E Series

E1050

10.0 Megapixels | 5X Optical Zoom | 3.0" LCD | Electronic Image Stabilization | Face Detection | Smile Detection | Blink Detection | 3200 ISO | Panorama | Red-Eye Removal

With all its advanced features, this camera gives you great pictures with just a touch.

Compact and stylish, the GE E1050 redefines the term "feature-rich." For starters, it offers the latest touch-screen panel technology that makes it fun and easy to take fabulous photos. Plus, the aspheric all-glass lens provides an ultra sharp image. The E1050 is our first camera to offer direct HDTV output, plus an optional GPS accessory.

With a spacious 3-inch high-resolution LCD screen (230,400 pixels), photo playback is a delightful experience. The GE E1050 comes with the latest auto-brightness LCD technology that ensures perfect screen visibility both indoors and outdoors.

Featuring a comprehensive 10-megapixel resolution, 5x optical zoom, 4.5x digital zoom, 22.5x combined zoom, and a 28mm wide angle lens, you won't find a camera that's more versatile … from tight close-ups to wide group shots.

Within the 23.5mm slim body design is a host of advanced features, including: In-Camera Panorama Stitching, Smile Detection, Blink Detection, Face Detection, Electronic Image Stabilization, Red-Eye Removal and an amazing 1280x720 MPEG-4 movie recording capability.

Hold the E1050 and see for yourself all it has to offer. Then you'll understand how this camera is taking point-and-shoot models to a whole new level.

Shown in black.
Also available:

- Red
- Silver

Exclusive Digital Camera Licensee

General Imaging™

E SERIES **E1050**

With all its advanced features, this camera gives you great pictures with just a touch.

Effective Image Sensor Pixels		10.5 Megapixels
Image Sensor		10.7 Megapixels ［1／2.33" Charge Coupled Device (CCD)］
Lens	Focal Length F =	5 mm（Wide）－ 25 mm（Tele）
	[35mm film equivalent]	[28 mm（Wide）－ 140 mm（Tele）]
	F number	F3.3（Wide）－ F4.9（Tele）
	Lens Construction	9 elements in 8 groups
	Optical Zoom	5x
	Focusing Range	Normal：60cm～∞
		Macro：(Wide) 5cm～∞
Anti-Handshake		Electronic Image Stabilization
Digital Zoom		4.5x digital zoom （Combined Zoom: 22.5x）
Number of Recording Pixels	Still Image	10MP: 3648×2736, (3:2)9MP: 3648×2432, (16:9)7MP: 3648×2052, 5MP: 2560×1920, 3MP: 2048×1536, 2MP: 1600×1200, 1MP: 1024×768, 0.3MP: 640×480
	Movie	1280×720pixels: 30fps, 640×480pixels: 30fps／15fps, 320×240pixels: 30fps／15fps
Image Compression		Best、Fine、Normal
DCF、DPOF（Ver1.1）Support		Yes
File Format	Still Image	Exif2.2（JPEG）
	Movie	Image Compression: MPEG4, Audio: G.711〔Monoaural〕
	Audio	WAVE〔Monoaural〕(Max 60 seconds)
Shooting Modes		Auto, Manual, Image Stabilization, Movie, Scene (Sport, Children, Indoor, Leaf, Snow, Sunset, Fireworks, Glass, Museum, Landscape, Night Landscape, Night Portrait), Panorama, Portrait
Start-Up Time		1.5 sec.
Detection Features		Face, Smile and Blink
Red-Eye Removal		Yes
GPS Support		Yes
Viewfinder		-
LCD Screen		3.0 inch (230.400 pixels) LTPS (low-temperature polycrystalline silicon) TFT color LCD
		Self-regulation brightness in the sun
ISO Sensitivity		Auto, ISO80／100／200／400／800／1600／3200
AF Method		Single AF, Multi-AF (TTL 9-point), Face-Detection, AF Assist Beam (On / Off)
Light Metering Method		Artificial Intelligence AE (Ai AE), Center-Weighted Average, Spot (Fixed to center of frame)
Exposure Control Method		ProgramAE (AE-lock available)
Exposure Compensation		± 2 EV in 1/3 Step increments
Shutter Speed		4 ～ 1／2000 second (Manual 30s)
Continuous Shooting		Approx. 1.8 fps （Large／Fine Mode）
Playback Modes		Single Photo, Index (4 / 9 / 16 thumbnails), Slide Show, Movie (Slow-Motion possible), Zoom (Approx. 2x～8x), Audio , Histogram Display
White Balance Control		Auto (AWB), [Daylight, Cloudy, Incandescent, Fluorescent , Fluorescent CWF , Manual]
Internal Flash （Shooting Range）		Auto / Red-Eye Reduction / Forced Flash / No Flash / Slow Synchro / Red-Eye Reduction+Slow Synchro
		Shooting Range Wide: Approx. 0.3m～3.2m ／ Tele: Approx. 0.3m～2.1m (ISO 400)
Recording Media		Internal Memory: 26MB
		SD Card ／ SDHC Card (Up to 4GB support)
Other Features		PictBridge、ExifPrint Support、Multi-language Support (11 languages)
Jacks		USB2.0 / AV-OUT (Integrated Proprietary Connector), HDTV
Power		Rechargeable Lithium-ion Battery GB-40 , 3.7V 1050mAh
Shooting Capability (Battery Performance)		Approx. 200 shots（based on CIPA Standards）
Operation Environment		Temperature: 0～40℃, Humidity: 0～90%
Body Material		Metal cover
Dimensions (W x H x D)		3.6 inch Width × 2.2 inch Height × .9 inch Depth (92.5mm Width × 57mm Height × 23.5mm Depth)
Weight		5.1 oz. (Approx. 145g)（Body only）
Supplied Accessories		Rechargeable Lithium-ion Battery, Battery Charger, USB Cable, AV Cable, Wrist Strap, CD-ROM, Manual, Quick Start Guide, Warranty Card

(Design and specifications are subject to change without notice)